AV3130

Arecont Vision megapixel technology... beyond imagination

3/1.3 Megapixel IP-camera

AV3130M (Day/Night)



Arecont Vision Advantages:

Superior Low Light Performance

• 1/2" color and monochrome CMOS sensors

leled High Definition Resolution - 2048x1536Ten times the resolution of IP VGA or analog cameras

• 1.3 MP B/W and 3 MP Color

gaPixel Image Ra

• Up to 15fps/30fps in 3/1.3 megapixel modes

• Zoom live or after-event while recording full field of view in HD ... replace PTZ devices

Reduced Overall System Cost

• Less cameras to install, less wiring, no external power (POE), less NVR licensing fees

• Comparable cost to IP VGA & analog cameras

• Can be selected for either live viewing or archiving purposes

- Simultaneous full field of view and Region-of-Interest (ROI)
- Image cropping allows streaming of full density partial images
- On-camera motion detection

MegaVideo® Series

Model Numbers:

AV3130M - Color and Day/Night

Imaging

- 3 megapixel color 2048(H) x 1536(V) 3.2µm
- 1.3 megapixel monochrome 1280(H) x 1024(V) 5.2µm
- 1/2" CMOS optical format
- Bayer mosaic RGB filter
- Minimum illumination of:
 - Color: 0.2 Lux @ F1.4
 - B/W: 0 Lux, IR sensitive
- Dynamic Range 61 dB
- Maximum SNR 49 dB

Full Field of View (FOV) Resolutions

• 2048(H)x1536(V)
 • 1024(H)x768(V)
 • 1280(H)x1024(V)
 • 640(H)x512(V)
 3 megapixel
 1/4 resolution
 1.3 megapixel
 1/4 resolution

Cropped Field of View Resolution

• 1920x1200 WUXGA • 1920x1080 HDTV-1080p • 1600x1200 2 MP 1.3 MP • 1280x1024 • 1280x720 HDTV-720p • 1024x768 XGA • 800x600 **SVGA** • 704x570 PAI • 704x480 NTSC • 640x480 VGA • 352x288 CIF • 320x240 SIF

Data Transmission

- Data Rate up to 55Mbps
- Video frame rate up to:
 - 15 fps @ 2048x1536
 - 20 fps @ 1920x1200
 - 22 fps @ 1920x1080
 - 24 fps @ 1600x1200
 - 32 fps @ 1280x1024
- Motion JPEG with 21 levels of quality
- TFTP and HTTP image transmission protocols
- 100Base-T Ethernet Network Interface

Programmability

- Auto Exposure (AE) and Gain Control (AGC) >120dB
- On-camera motion detection with 64 detection zones
- Auto backlight compensation
- Auto multi-matrix white balance
- 50/60Hz selectable flicker control
- Electronic pan, tilt, zoom (PTZ)
- Electronic image rotation 180° flip
- Resolution Windowing Down to 32x32 Pixels Window
- Programmable shutter to minimize motion blurring for low-light mode
- MoonLight™ mode extended exposure and proprietary noise cancellation
- Programmable resolution, brightness, saturation, gamma, sharpness, tint
- Picture-in-Picture: simultaneous delivery of full field of view and zoomed Images
- Bandwidth & storage savings by running at 1/4 resolution

Electrical

- General purpose opto-coupled input and output
- Power Over Ethernet (PoE): PoE 802.3af
- DC Input: auxiliary 15V-48V DC
- Power consumption 3.2 Watts maximum

Regulatory Approvals


• FCC, CE and RoHS compliant

Environmental

- Operating temperature 0°C (32 °F) to +50°C (122 °F)
- Storage temperature -20°C (-4°F) to +60°C (140°F)
- Humidity 0% to 90% (non condensing)

Mechanical

- 3"W (76 mm) x 2.5"H (63.5 mm) x 2.25"D (57mm) (w/o lens)
- 8.6 oz (243 grams) (w/o lens)
- C/CS lens mount



Housing Accessories:

Dome 4-I - Indoor 4" Vandal Dome Dome 4-O- Outdoor 4" Vandal Dome Dome 5-I - Indoor 5" Recessed Dome

HSG1-O-W - Outdoor Environmental Housing w/Heater/Blower

Lenses:

MPL4-10 MPL8-16 MPL4.0 MPL6.0

MPL8.0

* Other megapixel lenses are also available with Arecont Vision's housing options.



Revised on 12/10/09