

SurroundVideo® Omni G3

4 Remote Configurable Motorized Sensor Gimbals in an Omni-Directional All-in-One Solution

- 12 or 20 Megapixel (MP) H.264 All-in-One Remote Setup Omni-Directional Camera
- No Touch Setup: 4 Individual Camera Gimbals Each with a 2.8–6mm Motorized Lens That Can be Remotely Setup in Any Position Around a 360° Track
- Preset Positions to Create a 360°, 270°, or 180° Field of View
- Enhanced WDR™ (Wide Dynamic Range) up to 100dB at Full Resolution (Select Models)

Available Now



180° Panoramic

360° Panoramic

SurroundVideo® G5 Mini

Smaller Housing Models Now Up to 20 Megapixel

- 12 and 20MP H.264 All-in-One 180° or 360° Panoramic True Day/Night Indoor/Outdoor Dome IP Cameras
- Enhanced WDR™ up to 100dB at Full Resolution (Select Models)
- Faster Frame Rates versus Previous Generation
- New Easy-to-Install Housing Design

Available Now

MegaDome® UltraHD

12 Megapixel at 20fps!

- 12MP Ultra High Resolution Image Quality at 20 Frames per Second
- H.264 True Day/Night Indoor/Outdoor Dome IP Camera with Adjustable IR
- Capable of 4K Resolution at 30fps and 1080p Resolution at 60fps
- NightView™ for Strong Low Light Performance
- New Easy-to-Install Housing Design

Coming Soon



P-Iris Motorized Lens with IR

P-Iris Motorized Lens


Remote Setup (RS)

MegaDome® G3 Series

“No-Touch” Remote Setup Models, Installer-Friendly Design

- Remote Setup – No Touch Setup with a Varifocal Motorized Lens that can be Remotely Setup in Any Position with Pan, Tilt, Focus, and Zoom (G3 RS Models)
- Remote Focus/Zoom, P-Iris Lens (G3 Models)
- Loaded with Multiple Features and Options
- New Easy-to-Install Housing Design

Available Now



SNAPstream™ Technology
(Smart Noise Adaptation and Processing)

SNAPstream™ Advanced Compression Algorithm Reduces Bandwidth without Impacting Image Quality. Available on All Featured Products.

MegaVideo® UltraHD

12 Megapixel at 20fps, Multiple Motorized Lens Options

- 12 Megapixel (MP) Ultra High Resolution Image Quality at 20 Frames per Second
- Multiple Motorized P-Iris Lens Options to Choose From
- Capable of 4K Resolution at 30fps and 1080p Resolution at 60fps
- NightView™ for Strong Low Light Performance
- New HSG3 Housing is Available for Indoor/Outdoor Mounting Solutions

Coming Soon



MegaVideo® Flex

Ultra Low Profile Design Solution

- 1.2, 1080p, 3, and 5MP H.264 Remote Focus True Day/Night Indoor Tethered IP Cameras with Optional IR LEDs
- Camera Sensor and Main Unit can be Connected via a Micro-USB Cable up to 40ft in Length
- Enhanced WDR™ (Wide Dynamic Range) up to 100dB at Full Resolution (Select Models)
- Multiple Lens Options in a Single Camera Housing from 2.1mm to 16mm

Available Now

* Sold Separately

MicroDome® Duo

2 Motorized User-Configurable Sensors in an All-in-One Solution

- 4, 6, and 10MP H.264 All-in-One Remote Focus User-Configurable Multi-Sensor True Day/Night Indoor/Outdoor Dome IP Cameras
- Enhanced WDR™ up to 100dB at Full Resolution (Select Models)
- 2 Individual 3-Axis Camera Gimbals can be Positioned Independently
- Multiple Lens Options in a Single Camera Housing from 2.1mm to 16mm

Available Now



MicroDome® G2

Now with IR Models

- 1.2, 1080p, 3, and 5MP H.264 All-in-One True Day/Night Indoor/Outdoor Dome IP Cameras
- Enhanced WDR™ up to 100dB at Full Resolution (Select Models)
- IK-10 and IP66 Rated Surface Mount Models with Optional IR LEDs (-S Models)
- Multiple Lens Options in a Single Camera Housing from 2.1mm to 16mm
- Easy to Install with Innovative Spring Arm Design (-F Models)

Available Now



SNAPstream™ Technology
(Smart Noise Adaptation and Processing)

SNAPstream™ Advanced Compression Algorithm Reduces Bandwidth without Impacting Image Quality. Available on All Featured Products.